

THE CLAIMS

The claims of the application, as amended herewith, are:

Claims 1-11. (Cancelled)

Claim 12. (New) A saw frame comprising an elongate, substantially rigid back member, a handle portion, and an elongate swing arm pivotably connected to said back member at a connection point distal from said handle portion so as to be pivotable between an extended position, generally transverse to said back member, and a storage position aligned with said back member; said handle portion including at least a first blade-engaging element; said swing arm including at least a second blade-engaging element disposed distal from said connection point, and said back member including at least a third blade-engaging element disposed proximal to said connection point, and each of said blade-engaging elements being constructed to engage one end of a removably mounted saw blade; said first, second, and third blade-engaging elements being generally coplanar and located such that, with said swing arm in said extended position thereof, said second and third blade-engaging elements are commonly disposed on an arc circumscribing said first blade-engaging element.

Claim 13. (New) The saw frame of Claim 12 wherein said handle portion additionally includes a quick-release blade-tensioning mechanism operative to releasably apply, at said first blade-engaging element, a selectable amount of

tension to a mounted blade; and wherein said frame allows conversion, without need for adjustment of said selectable amount of tension, between a first configuration, with said swing arm in said extended position and a saw blade mounted between said first and second blade-engaging elements, and a second configuration with a saw blade mounted between said first and third blade-engaging elements.

Claim 14. (New) The saw frame of Claim 12 wherein said handle portion additionally includes a fourth blade-engaging element, wherein said swing arm additionally includes a fifth blade-engaging element, and wherein said fourth and fifth blade-engaging element are non-coplanar with said first, second, and third blade-engaging elements and are located such that, with said swing arm in said extended position thereof, said fifth blade-engaging element is disposed on an arc circumscribing said fourth blade-engaging element and having the radius of said arc circumscribing said first blade-engaging element.

Claim 15. (New) The saw frame of Claim 14 wherein said back member additionally includes a sixth blade-engaging element disposed proximal to said connection point, wherein said fourth, fifth, and sixth blade-engaging elements are mutually coplanar but non-coplanar with said first, second, and third blade-engaging elements, and wherein, with said swing arm in said extended position thereof, said fifth and sixth blade-engaging elements are commonly disposed on said arc circumscribing said fourth blade-engaging element.

Claim 16. (New) The saw frame of Claim 12 wherein each of said blade-engaging elements comprises a conical pin tapered toward and projecting from an orienting, blade-supporting surface.

Claim 17. (New) The saw frame of Claim 12 wherein said back member is substantially rectilinear.

Claim 18. (New) The saw frame of Claim 12 wherein said back member further includes an upwardly opening channel in which said swing arm is disposed in said storage position thereof.

Claim 19. (New) The saw frame of Claim 12 wherein said back member further includes a downwardly extending lobe proximal to said connection point, said third blade-engaging element being disposed on said lobe.

Claim 20. (New) The saw frame of Claim 19 wherein said lobe includes a bearing surface that limits the pivotable movement of said swing arm.

Claim 21. (New) The saw frame of Claim 12 wherein, with said swing arm in said extended position thereof, a first theoretical line extending between said first and second blade-engaging elements is disposed substantially parallel to an axis extending in the direction of elongation of said back member, and wherein a second theoretical line extending between said first and third blade-engaging

elements is angularly disposed with respect to said axis extending in the direction of elongation.

Claim 22. (New) The saw frame of Claim 21 where said back member is substantially rectilinear, and wherein said first theoretical line is substantially parallel to the longitudinal axis of said back member.

Claim 23. (New) The saw frame of Claim 12 additionally comprising a mounted saw blade.

Claim 24. (New) The saw frame of Claim 23 wherein said swing arm is in said extended position thereof, and said saw blade is mounted on said first and second blade-engaging elements.

Claim 25. (New) The saw frame of Claim 23 wherein said swing arm is in said storage position thereof, and said saw blade is mounted on said first and third blade-engaging elements.

Claim 26. (New) The saw frame of Claim 12 wherein said handle portion comprises a grip portion integrally formed with said back member.

Claim 27. (New) The saw frame of Claim 12 wherein said handle portion additionally includes a quick-release blade-tensioning mechanism operative to releasably apply tension to a mounted blade, acting through said first blade-engaging element.

Claim 28. (New) The saw frame of Claim 27 wherein said quick-release blade-tensioning mechanism comprises an operating lever pivotally connected to a lower part of said handle portion.

Claim 29. (New) A saw frame comprising an elongate, substantially rigid back member, a handle portion, and an elongate swing arm pivotally connected to said back member at a connection point distal from said handle portion so as to be pivotable between an extended position, generally transverse to said back member, and a storage position aligned with said back member; said handle portion including at least first and fourth blade-engaging elements, and a quick-release blade tensioning mechanism operative to releasably apply, at said first and fourth blade-engaging elements, a selectable amount of tension to a mounted blade; said swing arm including at least second and fifth blade-engaging elements, disposed distal from said connection point; and said back member including at least third and sixth blade-engaging elements, disposed proximal to said connection point, each of said blade-engaging elements being constructed to engage one end of a removably mounted saw blade; said first, second, and third blade-engaging elements being generally coplanar and located such that, with said swing arm in said extended position thereof, said second and third blade-engaging elements are commonly disposed on an arc circumscribing said first blade-engaging element; said fourth, fifth, and sixth blade-engaging elements being mutually coplanar, non-coplanar with said first, second, and third blade engaging-members, and located

such that, with said swing arm in said extended position thereof, said fifth and sixth blade engaging-members are commonly disposed on an arc circumscribing said fourth blade-engaging element; said back member additionally including a downwardly extending lobe proximal to said connection point, said third and sixth blade engaging-elements being disposed on said lobe and said lobe including a bearing surface that limits the pivotable movement of said swing arm; a first theoretical line, extending between said first and second blade-engaging elements with said swing arm in said extended position thereof, being disposed substantially parallel to an axis extending in the direction of elongation of said back member, and a second theoretical line, extending between said first and third blade-engaging elements, being angularly disposed with respect to said axis extending in the direction of elongation; said frame allowing conversion, without need for adjustment of said selectable amount of tension, between a first configuration, with said swing arm in said extended position thereof and a saw blade mounted between said first and second blade-engaging elements, and a second configuration with a saw blade mounted between said first and third blade-engaging elements.

Claim 30. (New) The saw frame of Claim 29 wherein said quick-release blade tensioning mechanism comprises an operating lever pivotably connected to a lower part of said handle portion.